

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number  
**WO 2005/089977 A1**

(51) International Patent Classification<sup>7</sup>: **B21D 53/26**,  
B60B 3/10

(21) International Application Number:  
PCT/US2005/009206

(22) International Filing Date: 18 March 2005 (18.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/554,214 18 March 2004 (18.03.2004) US

(71) Applicant (for all designated States except US): **HAYES  
LEMMERZ INTERNATIONAL, INC.** [US/US]; 15300  
Centennial Drive, Northville, MI 48167 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MCCORRY,**


Patrick [US/US]; 649 Herald, Plymouth, MI 48170 (US).  
**CZARNIECKI, Tom** [US/US]; 228 Sheridan, Dearborn,  
MI (US). **CSAPO, Monty** [US/US]; 8984 Parent, Livonia,  
MI (US). **DUFFIELD, Todd** [US/US]; 609 Cashew,  
Westland, MI (US). **GRUTGEN, Matthias** [DE/DE];  
Tombergstrasse 6, 53639 Konigswinter (DE). **KRAMER,  
Frank** [DE/DE]; Schubertstrasse 18, 51145 Koln (DE).  
**COLEMAN, Alan** [US/US]; 13182 Kimberly, Southgate,  
MI 48195 (US).

(74) Agent: **PAVELKO, Douglas, V.**; MacMillan, Sobanski  
& Todd, LLC, One Maritime Plaza, 4th Floor, 720 Water  
Street, Toledo, OH 43604 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

[Continued on next page]

(54) Title: FABRICATED VEHICLE WHEEL AND METHOD FOR PRODUCING SAME



(57) Abstract: This invention relates to a fabricated vehicle wheel and method for producing the same. The wheel includes a rim and a disc secured to the rim. The disc includes a plurality of outwardly extending spokes, an outer rim connecting flange defining a side edge surface and a window formed therein between adjacent pairs of spokes and having a predetermined shape defined by the adjacent pairs of spokes and the side edge surface of the rim connecting flange such that each of the windows extends to an outermost periphery of the wheel disc, at least one of the windows includes at least a first window portion and a second window portion, the first window portion being formed by a first piercing operation and the second window portion being formed by a second piercing operation.



MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

**(84) Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.